



## Male female Adaptors

MFA - G - G

Dimensions in mm

DIN Fittings

Male thread : BSPP (G) - ISO 228  
Female thread : BSPP (G)



| Part No.  | Pressure | Male Thread G | Female Thread G i | l    | i  | S1 | Ød | Ød3 | t 3  |
|-----------|----------|---------------|-------------------|------|----|----|----|-----|------|
| MFAG01G02 | 630 bar  | G 1 / 8 A     | G 1 / 4           | 31   | 8  | 19 | 4  | 14  | 17.0 |
| MFAG01G03 | 630 bar  | G 1 / 8 A     | G 3 / 8           | 32   | 8  | 24 | 4  | 14  | 17.0 |
| MFAG02G01 | 630 bar  | G 1 / 4 A     | G 1 / 8           | 28   | 12 | 19 | 5  | 18  | 12.0 |
| MFAG02G03 | 630 bar  | G 1 / 4 A     | G 3 / 8           | 36   | 12 | 24 | 5  | 18  | 17.0 |
| MFAG02G04 | 630 bar  | G 1 / 4 A     | G 1 / 2           | 40   | 12 | 30 | 5  | 18  | 20.0 |
| MFAG02G06 | 630 bar  | G 1 / 4 A     | G 3 / 4           | 43   | 12 | 36 | 5  | 18  | 22.0 |
| MFAG03G01 | 630 bar  | G 3 / 8 A     | G 1 / 8           | 22.5 | 12 | 22 | -- | 22  | 8.0  |
| MFAG03G02 | 630 bar  | G 3 / 8 A     | G 1 / 4           | 36   | 12 | 22 | 8  | 22  | 17.0 |
| MFAG03G04 | 630 bar  | G 3 / 8 A     | G 1 / 2           | 41   | 12 | 30 | 8  | 22  | 20.0 |
| MFAG03G06 | 400 bar  | G 3 / 8 A     | G 3 / 4           | 44   | 12 | 36 | 8  | 22  | 22.0 |
| MFAG04G02 | 630 bar  | G 1 / 2 A     | G 1 / 4           | 24   | 14 | 27 | -- | 26  | 12.0 |
| MFAG04G03 | 630 bar  | G 1 / 2 A     | G 3 / 8           | 36   | 14 | 27 | 12 | 26  | 17.0 |
| MFAG04G06 | 400 bar  | G 1 / 2 A     | G 3 / 4           | 46   | 14 | 36 | 12 | 26  | 22.0 |
| MFAG04G08 | 400 bar  | G 1 / 2 A     | G 1               | 49   | 14 | 41 | 12 | 26  | 24.5 |
| MFAG04G10 | 250 bar  | G 1 / 2 A     | G1.1 / 4          | 53   | 14 | 55 | 10 | 26  | 26.5 |
| MFAG06G02 | 400 bar  | G 3 / 4 A     | G 1 / 4           | 26.0 | 16 | 32 | -- | 32  | 12.0 |
| MFAG06G03 | 400 bar  | G 3 / 4 A     | G 3 / 8           | 26.0 | 16 | 32 | -- | 32  | 12.0 |
| MFAG06G04 | 400 bar  | G 3 / 4 A     | G 1 / 2           | 41   | 16 | 32 | 16 | 32  | 20.0 |
| MFAG06G08 | 400 bar  | G 3 / 4 A     | G 1               | 51   | 16 | 41 | 16 | 32  | 24.5 |
| MFAG06G10 | 250 bar  | G 3 / 4 A     | G1.1/4            | 55   | 16 | 55 | 16 | 32  | 26.5 |
| MFAG06G12 | 250 bar  | G 3 / 4 A     | G1.1/2            | 57   | 16 | 60 | 16 | 32  | 28.5 |
| MFAG08G02 | 400 bar  | G 1 A         | G 1 / 4           | 29.0 | 18 | 41 | -- | 39  | 12.0 |
| MFAG08G03 | 400 bar  | G 1 A         | G 3 / 8           | 29.0 | 18 | 41 | -- | 39  | 12.0 |
| MFAG08G04 | 400 bar  | G 1 A         | G 1 / 2           | 29.0 | 18 | 41 | -- | 39  | 14.0 |
| MFAG08G06 | 400 bar  | G 1 A         | G 3 / 4           | 47   | 18 | 41 | 20 | 39  | 22.0 |
| MFAG08G10 | 250 bar  | G 1 A         | G1.1/4            | 57   | 18 | 55 | 20 | 39  | 26.5 |
| MFAG08G12 | 250 bar  | G 1 A         | G1.1/2            | 59   | 18 | 60 | 20 | 39  | 28.5 |
| MFAG10G04 | 250 bar  | G1.1/4 A      | G 1 / 2           | 32.0 | 20 | 50 | -- | 49  | 14.0 |
| MFAG10G06 | 250 bar  | G1.1/4 A      | G 3 / 4           | 32.0 | 20 | 50 | -- | 49  | 16.0 |
| MFAG10G08 | 250 bar  | G1.1 / 4 A    | G 1               | 52   | 20 | 50 | 25 | 49  | 24.5 |
| MFAG10G12 | 250 bar  | G1.1 / 4 A    | G1.1/2            | 60   | 20 | 60 | 25 | 49  | 28.5 |
| MFAG12G04 | 250 bar  | G1.1/2 A      | G 1 / 2           | 36.0 | 22 | 55 | -- | 55  | 14.0 |
| MFAG12G06 | 250 bar  | G1.1/2 A      | G 3 / 4           | 36.0 | 22 | 55 | -- | 55  | 16.0 |
| MFAG12G08 | 250 bar  | G1.1/2 A      | G 1               | 36.0 | 22 | 55 | -- | 55  | 18.0 |
| MFAG12G10 | 250 bar  | G 1 1 / 2     | G1.1/4            | 58   | 22 | 55 | 32 | 55  | 26.5 |