


Hex head Plug with O-Ring (ISO 6149-4)
Male thread : Metric (M) - ISO 261



Part No.	Working Pressure (bar)	M Male thread Metric	ød3	i	l1	S1	O-Ring ID x CSD	Tightening Torque N-m
VSTM100	630	M10 x 1.0	13.8	9.5	17.0	14	8.1 x 1.6	20
VSTM120	630	M12 x 1.5	16.8	11.0	18.5	17	9.3 x 2.2	35
VSTM140	630	M14 x 1.5	18.8	11.0	19.5	19	11.3 x 2.2	45
VSTM160	630	M16 x 1.5	21.8	12.5	22.0	22	13.3 x 2.2	55
VSTM180	630	M18 x 1.5	23.8	14.0	24.0	24	15.3 x 2.2	70
VSTM220	630	M22 x 1.5	26.8	15.0	26.0	27	19.3 x 2.2	100
VSTM270	400	M27 x 2.0	31.8	18.5	31.5	32	23.6 x 2.9	170
VSTM300	400	M30 x 2.0	35.8	18.5	33.0	36	26.6 x 2.9	215
VSTM330	400	M33 x 2.0	40.8	18.5	34.0	41	29.6 x 2.9	310
VSTM420	250	M42 x 2.0	49.8	19.0	36.5	50	38.6 x 2.9	330
VSTM480	250	M48 x 2.0	54.8	21.5	40.0	55	44.6 x 2.9	420
VSTM600	250	M60 x 2.0	64.8	24.0	44.5	65	56.6 x 2.9	500